

SNT12-230V/12V DC-2 A and SNT12-230V/24V DC-1 A



| | | |
|-------------------------------|---|---|
| | - | + |
| SEC (+/-) 24V DC / 1A | | |
| PRI (L/N) 207-230V/50-60Hz | | |
| | N | L |

Rated capacity 24 W. Standby loss 0.2 watt only.

Modular devices for DIN 60715 TH35 rail mounting. 2 modules = 36 mm wide, 58 mm deep. At a load of more than 50 % of the rated capacity and always if there are adjacent switching power supply units from 12 W rated capacity and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.

Input voltage 230V (-20% up to +10%).

Efficiency 12V DC 83%, 24V DC 87%.

Stabilised output voltage $\pm 1\%$, low residual ripple.

Short-circuit proof.

Overload protection and over-temperature switch-off by means of switching off with automatic switching-on after fault clearance (autorecovery function).

Technical data page I4. Housing for operating instructions GBA12 page Z5.

SNT12-230V/12V DC-2A
SNT12-230V/24V DC-1A

EAN 4010312301135
EAN 4010312301142

54,60 €/pc.
54,60 €/pc.

Recommended retail prices excluding VAT.